# **Product Specifications**



# 3/16" x 5-1/2" Carbide Tipped Hammer Drill Bit

Part Number CD3165 Category Number 4570 UPC 781002145103

Carbide Tipped Masonry Drill Bits are used in conjunction with concrete screws. They feature a flat shank that helps prevent bit slippage and hold tight tolerances that are critical to precision anchoring. They are suitable for masonry, brick, block and concrete.



## **Physical Characteristics**

Туре	Hammer Drill
Shank Type	Tang Shank
Tip Style	Carbide
Size	3/16" x 5-1/2"
Shank Size	5/32"
Anchor Diameter	1/4"
Bit Diameter	3/16"
Overall Length	5-1/2"
Material	High Speed Steel
Finish	Black Oxide
Number of Flutes	1

### **Packaging Details**

Standard Qty	10
Price Per	1
Package Length	7.87
Package Width	2.99
Package Height	.00
Net Weight	0.005
Package Weight	.05

#### **Performance Data**

Applications	For Hex and Phillips Concrete Screws	
Special Features	Carbide Tip, Close Tolerances, Tang Shank, Made Specifically for Installing Concrete Screws	

#### Certifications

RoHS Compliant	No

L.H. Dottie Co. Commerce, CA 323-725-1000 www.lhdottie.com