

# Product Specifications



## 3/8"-16 Drop-In Anchor

Part Number DA38

Category Number 4500

UPC 781002276050

Drop-In Anchors are manufactured with an internally threaded, all-steel exterior shell that features an expansion cone insert used to anchor into the concrete. They are intended to be used in concrete materials only and can be used with any head style screw. The screw can easily be removed, loosened, or re-tightened if needed. Common applications include, pipe hanging, overhead anchoring, hanging strut, sprinkler systems and removable anchoring points.



### Physical Characteristics

|                              |              |
|------------------------------|--------------|
| Install Tool                 | AT38         |
| Anchor Type                  | Drop In      |
| Thread Type                  | UNC          |
| Anchor Diameter              | 3/8"         |
| Anchor Length                | 1-9/16"      |
| Thread Length                | 5/8"         |
| Thread Per Inch              | 16           |
| Thread Pitch\Thread Per Inch | 3/8"-16      |
| Material                     | Carbon Steel |
| Finish                       | Zinc Plated  |

### Performance Data

|                         |  |
|-------------------------|--|
| Pre-Drill Size          | 1/2"   |
| Minimum Embedment Depth | 1-9/16"  |
| Applications            | Pipe Hanging, Overhead Anchoring, Hanging Strut, Sprinkler Systems and Removable Anchor Points |
| Special Features        | Zinc Plated, Easy Bolt Installation/Removal, Lip for Flush Installation, Expansion Cone Insert |
| Cement Type             | Various PSI  |

### Packaging Details

|                |        |
|----------------|--------|
| Standard Qty   | 50     |
| Master Qty     | 500    |
| Price Per      | 100    |
| Package Length | 5.60   |
| Package Width  | 4.20   |
| Package Height | 2.60   |
| Net Weight     | 0.0637 |
| Package Weight | 3.19   |

### Certifications

|                |     |
|----------------|-----|
| RoHS Compliant | Yes |
|----------------|-----|