

Product Specifications



3/8"-16 Stainless Steel Drop-In Anchor

Part Number DAS38
Category Number 4310
UPC 781002702627



Stainless Steel Drop-In Anchors are manufactured with an internally threaded, all-stainless steel exterior shell that features an expansion cone insert used to anchor into the concrete. They are intended to be used in concrete materials only and can be used with any head style screw. The screw can easily be removed, loosened, or re-tightened if needed. Common applications include, pipe hanging, overhead anchoring, hanging strut, sprinkler systems and removable anchoring points. They are available in 18-8 stainless steel and can be manufactured to order in 316 stainless steel.

Physical Characteristics

Install Tool	AT38
Anchor Type	Drop In
Thread Type	UNC
Anchor Diameter	3/8"
Anchor Length	1-9/16"
Thread Length	5/8"
Thread Per Inch	16
Thread Pitch\Thread Per Inch	3/8"-16
Material	304 Stainless Steel

Packaging Details

Standard Qty	50
Master Qty	500
Price Per	100
Package Length	5.59
Package Width	4.09
Package Height	2.60
Net Weight	0.063
Package Weight	3.15

Performance Data

Pre-Drill Size	1/2"
Minimum Embedment Depth	1-9/16"
Applications	Pipe Hanging, Overhead Anchoring, Hanging Strut, Sprinkler Systems and Removable Anchor Points
Special Features	Corrosion Resistant, Easy Bolt Installation/Removal, Lip for Flush Installation, Expansion Cone Insert
Cement Type	Various PSI

Certifications

RoHS Compliant	Yes
----------------	-----