

# Product Specifications



## 3/4" Insulated Ground Bushing w/ Lay In Lug

Part Number GBL75

Category Number 5600

UPC 781002104056

Insulated Ground Bushings are used to fasten and ground threaded rigid conduit or IMC to an enclosure. They feature a Zinc/Aluminum body and a 90° Copper/Aluminum dual rated lay in lug that is intended for grounding jumper to neutral bus bar.



### Physical Characteristics

Type	Insulated Ground Bushing
Style	Lay In Lug
Size	3/4"
Connection	Threaded
Material	Zinc/Aluminum
Insulation	Nylon Insulator

### Packaging Details

Standard Qty	25
Master Qty	250
Price Per	100
Package Length	3.70
Package Width	5.30
Package Height	5.00
Net Weight	0.082
Package Weight	2.05

### Performance Data

Insulation	Nylon Insulator
Applications	Terminates Threaded Rigid Conduit/IMC To an Enclosure
Special Features	194°F Copper/Aluminum Dual Rated Lay In Lug, 302°F Rated Nylon Insulator
For Use With	Rigid/IMC Conduit

### Certifications

RoHS Compliant	Yes
Industry Standard	UL Listed

L.H. Dottie Co. Commerce, CA 323-725-1000 [www.lhdottie.com](http://www.lhdottie.com)