Product Specifications



3-1/2" Straight Insulated Die Cast Liquid Tight Connector

Part Number LT350I Category Number 5460 UPC 781002111450

Insulated Die Cast Liquid tight connectors are used to connect metallic and non-metallic liquid tight conduit to a weatherproof outlet box and various other electrical enclosures.



Physical Characteristics

Туре	Liquid Tight Connector
Style	Straight Insulated
Thread Type	NPT
Size	3-1/2"
Connection	Threaded
Material	Zinc Die Cast
Insulation	Sealing Ring

Packaging Details

Standard Qty	1
Price Per	100
Package Length	7.56
Package Width	5.75
Package Height	5.67
Net Weight	3.55
Package Weight	3.55

Performance Data

Temperature Rating	Up to 194°F
Insulated	Yes
Insulation	Sealing Ring
Applications	Terminates Liquid-Tight Flexible Metal and Non-Metal Type B Conduit to a Weatherproof Box or other Electrical Enclosures
Special Features	Oil Tight, Liquid Tight, Rain Tight, Concrete Tight
For Use With	Liquid-Tight Flexible Metal and Non-Metal Type B Conduit
Environmental Conditions	Wet Locations

Certifications

RoHS Compliant	Yes
Industry Standard	UL Listed