# **Product Specifications**



## 3/8" x 3" Sleeve Anchor w/ Hex Nut

Part Number SA38300 Category Number 4550 UPC 781002593409

Sleeve Anchors are a preassembled expanding anchor manufactured for use in concrete, cement, block, thin wall/solid concrete, brick or stone. Due to it's unique design, it can also be used in soft concretes because the compression load can be distributed over a longer length. It comes in both acorn and hex head and can be manufactured in stainless steel upon request. For installation instructions and weight loads, reference technical data sheet.

### **Physical Characteristics**

Anchor Type	Sleeve
Nut Type	Hex
Thread Type	UNC
Anchor Diameter	3/8"
Head Diameter	7/8"
Anchor Length	3-5/16"
Thread Length	3"
Thread Per Inch	16
Thread Pitch\Thread Per Inch	3/8"-16
Material	Carbon Steel
Finish	Zinc Plated

### Packaging Details

Standard Qty	50
Master Qty	250
Price Per	100
Package Length	6.40
Package Width	5.00
Package Height	3.50
Net Weight	0.106
Package Weight	5.30

#### **Performance Data**

Pre-Drill Size	3/8"
Minimum Embedment Depth	1-1/2"
Applications	Normal and Lightweight Concrete, Soft Concrete
Special Features	Pre-Assembled, Single Piece All Steel Sleeve, Versatile Use, Can Be Installed Through the Fixture
Cement Type	Various PSI

#### Certifications

L.H. Dottie Co. Commerce, CA

CA 323-725-1000

www.lhdottie.com