# **Product Specifications**



## 5/16" x 1-1/2" Sleeve Anchor w/ Hex Nut

Part Number SA516112 Category Number 4550 UPC 781002593348

Sleeve Anchors are a preassembled expanding anchor manufactured for use in concrete, cement, block, thin wall/solid concrete, brick or stone. Due to it's unique design, it can also be used in soft concretes because the compression load can be distributed over a longer length. It comes in both acorn and hex head and can be manufactured in stainless steel upon request. For installation instructions and weight loads, reference technical data sheet.

### **Physical Characteristics**

Anchor Type	Sleeve
Nut Type	Hex
Thread Type	UNC
Anchor Diameter	5/16"
Head Diameter	11/16"
Anchor Length	1-13/16"
Thread Length	1-1/2"
Thread Per Inch	18
Thread Pitch\Thread Per Inch	3/8"-16
Material	Carbon Steel
Finish	Zinc Plated

### Packaging Details

Standard Qty	100
Master Qty	600
Price Per	100
Package Length	5.80
Package Width	4.40
Package Height	3.20
Net Weight	0.0395
Package Weight	3.95

#### **Performance Data**

Pre-Drill Size	5/16"
Minimum Embedment Depth	1-1/4"
Applications	Normal and Lightweight Concrete, Soft Concrete
Special Features	Pre-Assembled, Single Piece All Steel Sleeve, Versatile Use, Can Be Installed Through the Fixture
Cement Type	Various PSI

#### Certifications

RoHS Compliant	
	Yes

L.H. Dottie Co. Commerce,

Commerce, CA 323-725-1000

www.lhdottie.com