

# Product Specifications



## 1/4" Long Lag Shield

Part Number SLS14  
Category Number 4450  
UPC 781002312307

Lag Shields are a two piece die cast anchor that allows for lag screws to be used in materials such as mortar joints, poured concrete, brick and concrete blocks. After drilling the hole the anchor installs with finger pressure or light taps. The lag shield is manufactured in two different lengths; long and short. The shorter style is utilized for harder masonry materials that reduce drilling time, whereas the longer version is used for increased strength in softer or weaker masonry materials.



### Physical Characteristics

Anchor Type	Lag Shield
Anchor Diameter	1/4"
Anchor Length	1-1/2"
Material	Zamac Alloy

### Packaging Details

Standard Qty	50
Master Qty	500
Price Per	100
Package Length	5.40
Package Width	4.10
Package Height	2.60
Net Weight	0.0316
Package Weight	1.58

### Performance Data

Tensile Strength (lb)	1600 lbs
Pre-Drill Size	1/2"
Minimum Embedment Depth	1-1/2"
Applications	Mortar Joints, Poured Concrete, Brick, Concrete Blocks
Special Features	Internally Threaded, Easy Lag Screw Installation/Removal, Available in Short and Long Styles

### Certifications

RoHS Compliant	No
----------------	----