

DWTT.E142707 - CONDUIT FITTINGS

Conduit Fittings

See General Information for Conduit Fittings

L H DOTTIE CO

6131 GARFIELD AVE
COMMERCE, CA 90040-3610 USA

E142707

Bushings Model(s) R364, R365, R366

Compression connectors, rigid Model(s) NT100, NT100I, NT125, NT125I, NT150, NT150I, NT200, NT200I, NT50, NT50I, NT75, NT75I

Compression couplings, rigid Model(s) NTC100, NTC125, NTC150, NTC200, NTC50, NTC75

Conduit Nipples Model(s) C-1210

Connectors, flexible conduits Model(s) SSQ90-100, SSQ90-125, SSQ90-150, SSQ90-200, SSQ90-250, SSQ90-300, SSQ90-350, SSQ90-38, SSQ90-400, SSQ90-50, SSQ90-75

Connectors, flexible metal conduits Model(s) SSQ-100, SSQ-125, SSQ-150, SSQ-200, SSQ-250, SSQ-300, SSQ-350, SSQ-38, SSQ-400, SSQ-50, SSQ-75

Connectors, for liquid-tight flexible metal conduits, type 2 Model(s) SL100I, SL125I, SL150I, SL200I, SL250I, SL300I, SL350I, SL400I, SL45100, SL45100I, SL45125, SL45150, SL45150I, SL45200, SL45250I, SL45300I, SL45400I, SL4550, SL4550I, SL4575, SL4575I, SL50I, SL75I, SL90100, SL90100I, SL90125, SL90125I, SL90150, SL90150I, SL90200, SL90250I, SL90300I, SL90350I, SL9038, SL90400I, SL9050, SL9050I, SL9075, SL9075I

Connectors, for rigid metal conduits Model(s) NT200, NT200I, NT250I, NT350I

Connectors, for rigid metal or IMC conduits Model(s) NT100, NT100I, NT125, NT125I, NT150, NT150I, NT300I, NT400I, NT50, NT50I, NT75, NT75I

Connectors, liquid-tight flexible metal conduits Model(s) LH-LTA350I, LH-LTA400I, LT 037, LT 037 I, LT 050, LT 050 I, LT 075, LT 075 I, LT 100, LT 100 I, LT 125, LT 125 I, LT 150, LT 150 I, LT 200, LT 200 I, LT 250, LT 250 I, LT 300, LT 300 I, LT 350, LT 350 I, LT 400, LT 400 I, LT90-037, LT90-037 I, LT90-050, LT90-050 I, LT90-075, LT90-075 I, LT90-100, LT90-100 I, LT90-125, LT90-125 I, LT90-150, LT90-150 I, LT90-200, LT90-200 I, LT90-250, LT90-250 I, LT90-300, LT90-300 I, LT90-350, LT90-400 I

Connectors, liquid-tight, flexible metal conduits, type 2 Model(s) SL100, SL10045, SL10045I, SL10090, SL10090I, SL100I, SL125, SL12545, SL12545I, SL12590, SL12590I, SL125I, SL150, SL15045, SL15045I, SL15090, SL15090I, SL150I, SL200, SL20045, SL20045I, SL20090, SL20090I, SL38, SL3845, SL3845I, SL3890, SL3890I, SL38I, SL50, SL5045, SL5045I, SL5090, SL5090I, SL50I, SL75, SL7545, SL7545I, SL7590, SL7590I, SL75I

Connectors, metallic and nonmetallic, liquid-tight flexible conduit Model(s) LT-100, LT-100-I, LT-125, LT-125-I, LT-150, LT-150-I, LT-200, LT-200-I, LT-250, LT-300, LT-350, LT-38, LT-38-I, LT-400, LT-50, LT-50-I, LT-75, LT-75-I, LT90-100, LT90-100-I, LT90-125, LT90-125-I, LT90-150-I, LT90-200, LT90-200-I, LT90-250, LT90-300, LT90-350, LT90-38, LT90-38-I, LT90-400, LT90-50, LT90-50-I, LT90-75, LT90-75-I

Couplings, for rigid metal conduit Model(s) NTC200, NTC250, NTC300, NTC400

Couplings, liquid tight Model(s) CF1, CF2, CF3

Couplings, liquid-tight, for rigid metal conduit or IMC to IMC Model(s) NTC100, NTC125, NTC150, NTC50, NTC75

Elbows Model(s) PE1, PE1G, PE2, PE2G, PE3, PE3G

Hubs, for use with threaded rigid conduits Model(s) WTH-100, WTH-125, WTH-150, WTH-200, WTH-250, WTH-300, WTH-350, WTH-400, WTH-50, WTH-75

Liquid-tight locknuts Model(s) LNS100, LNS125, LNS150, LNS200, LNS250, LNS300, LNS350, LNS400, LNS50, LNS75

Nipples Model(s) CN-100, CN-125, CN-150, CN-200, CN-250, CN-300, CN-350, CN-400, CN-50, CN-75, ON-100, ON-125, ON-150, ON-200, ON-50, ON-75

Nipples, offset Model(s) ON-050, ON-075, ON-250, ON-300

Reducer bushings Model(s) R352, R353, R354, R355, R356, R357, R358, R359, R360, R361, R362, R363, R364, R365, R366

Reducing Bushings Model(s) R352, R353, R354, R355, R356, R357, R358, R359, R360, R361, R362, R363, R364, R365, R366, R367, R368, R369, R370, R371, R372, R373, R374, R375, R376

Sealing locknuts Model(s) LNS100, LNS125, LNS150, LNS200, LNS50, LNS75

NOTE - Provided with or without suffix B, GT or M

Last Updated on 2019-11-21

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"